

Triona Auto Repair & Maintenance Equipment Offer

No.	Name	Model	Picture	Description	Packing Volume	Unit Price (EUR)	Sets
						EX.Work	
10	Car Collision Repair Bench	TR-F200		Specification Length: 5600MM; Width: 2100MM; Height 520MM Pulling capacity: 95KN Air supply required: 0.8MPA Radius of pulling: 360° Max. load: 3500KG Total weight: 2350KG	5CMB	5375.00	
11		TR-D200		Specification: Workplace length: 7000mm; Width: 4500mm Rail height: 40mm Max. pulling force: 10KN Air force: 6-8MPA Small puller force: 60KN		3530.00	
12	High Pressure Car Wash Machine(Cold-hot water type)	HDS 13/20-4 S *EU-I		Water flow capacity: 600-1300L/H; Pressure: 30-200/3-20; Max. water temperature: 80-155; Power consumption: 9.3KW; Oil consumption: 8.3KW; Oil tank: 25L; Weight: 186; Packing size: 1330*750*1060.		9832.00	
13		ZDT-1115		Power supply: 220V, 50Hz; Power consumption: 2-8KW; Water temperature: 30-75℃; Water flow capacity: 2.5-3L/min; Air pressure: 6-8bar; Weight: 27Kg; Packing size: 500*320*1500.		980.00	
14		ZDT-3104		Tank capacity: 70L; Pallet: 10L Oil collection height: 1.65m; Oil pumping speed: 0.6-1.6L/min; Working pressure: 7-8bar; Air consumption: 200L/min	0.48*0.55*0.86 5mm(L*W*H) Gross	320.00	

14	Waste Oil Collection Device	ZDT-3187		Working pressure: 7-8bar; Air consumption: 200L/min; Vacuum: 0-0.8bar; Oil pumping pipe: 1.5m Oil extraction pressure: 1bar; Oil extraction pipe length: 1.5m	weight/net weight: 25/21KG	320.00	
15		ZDT-3181		Tank capacity: 70L; Pallet: 10L Oil collection height: 1.65m; Oil pumping speed: 0.6-1.6L/min; Working pressure: 7-8bar Air consumption: 200L/min; Vacuum: 0-0.8bar Oil pumping pipe: 1.5m; Oil extraction pressure: 1bar Oil extraction pipe length: 1.5m	0.55*0.45*0.86 5mm(L*W*H) Gross weight/net weight: 24/20KG	195.00	
16	Tool Trolley	G-204		Size: 760*420*870mm(L*W*H); Weight: 29KG; Loading capacity: 100KG; Steel thickness: 1.0mm 4 Drawers		310.00	
17		G-205		Size: 760*420*880mm(L*W*H); Weight: 49.5KG; Loading capacity: 120KG; Steel thickness: 1.0mm 5 Drawers		352.00	
18	Metal service table	GP-315A		Dimension: 150*75*81CM Net weight: 46KG Hook as optional Standard configuration with 16 hooks		410.00	
19	Tyre changer	U-226		Power supply: 220V/380V, 50Hz Motor power: 0.75kw/ 0.55kw/1.1kw Max. wheel diameter: 41"/1040mm Max. wheel width: 14"/355mm; Rotation speed: 6rpm; Bead breaker force: 2500Kg (5500lbs) Working Pressure: 8bar; Noise: ≤70dB; Packing size: 960*760*930mm;1370*450*350mm.		2060.00	
				Power supply: 220V/380V, 50Hz; Motor power: 0.75kw/ 1.1kw			

20		ZDT-C22HT		Outside clamping: 10" - 21"; Inside clamping: 12" - 24"; Max. wheel diameter: 44"/1120mm; Max. wheel width: 14"/360mm; Rotation speed: 6rpm; Bead breaker force: 2500Kg (5500lbs); Working Pressure: 6-8bar;; Net weight: 380kg; Max. Torque: 1078Nm (110kg.m).		2070.00	
21	Wheel Balancer	U-828		Max. wheel weight: 65KG; Motor power: 0.2KW/0.37KW;; Power supply: 220V/110V; Rim width: 265-615mm/10"-24" Rim diameter: 40-510mm/1.5"-20" Inspection time: 8 Sec; Accuracy: ±1g; Noise: ≤70dB; Packing size: 960*760*1160mm.		940.00	
22		ZDT-B75		Motor power: 0.2-0.35kw Power supply: 220V/110V 50Hz/60Hz Balance speed: 200rpm; Balance accuracy: ±1g; Rim diameter: 40-510mm/1.5"-20"; Rim width: 254-615mm/10"-24"; Max. wheel diameter: 940mm/37"; Max. wheel weight: 65kg; Noise: <70dB; Weight: 140kg.		982.00	
23	Tools	58TR09004		Total 58/65/86/121/151 Pcs.optional Personalized design.		182.00	
24	Hydarulic engine stand	XH0303-2A		Capacity: 0.5Ton Minimum height(mm): 1290 Maximum height(mm): 1780 Package: 33Kgs/35Kgs wooden cases		332.00	
25		XH1701		Used for the repairing of the engine which not exceed 800Kg;		169.00	

26	Hydraulic Jack	T83002		Capacity: 3Ton Minimum height: 135mm Lifting height: 365mm Maximum height: 500mm Net weight/gross weight: 28Kgs/30Kgs Packing size: 690*375*210mm(L*W*H)		106.00	
27		XH-1005		Capacity: 5Ton Minimum height: 160mm Maximum height: 600mm Net weight/gross weight: 88Kgs/1010Kgs Packing size: 1540*420*275mm(L*W*H)		384.00	
28	Hydraulic trolley			Capacity: 5Ton Minimum height: 160mm Maximum height: 600mm Net weight/gross weight: 88Kgs/1010Kgs Packing size: 1540*420*275mm(L*W*H)		485.00	
28	Engine crane	XH2403		Capacity: 2Ton Arm range: 1050-1590mm Lifting range: 0-2360mm Package: 75Kgs/78Kgs		284.00	
29	Engine & Gearbox pre-assembly platform,AGV					1945.00	
30	Gasoline fluid filling machine			Without filling pipe and tank		1920.00	
31	Gearbox fluid filling machine			1) Working voltage: DC12V 2) Power consumption: 0.35kw 3) Weight: 62kg 4) Size: 605*500*1140mm(L*W*H)		1312.00	

32							
33	Repare Creecer	ZDY-0880		Size: 1020*470*120mm; Loading capacity: 200Kg; Thickness: 28mm; Height: 60mm; Gross/net weight: 6.5/6Kg		92.00	
345	Spray gun wash machine	ZDT-808X		Working pressure: 40-60PSI; Air consumption: 2-4CFM; Pump: pneumatic diaphragm pump; Inside size of the box: 600*550*400mm; Packing size: 675*525*710mm; Gross/net weight: 42/40KG.		872.00	
35	Spare parts wash machine	ZDT-25085		Pruge tank volume: 135L; With strainer and brushes; Working pressure: 1.2kg; Inside size: 900*500*300mm; Heating system as optional.		470.00	
36	Spray nozzle wash machine	ZDT-600		Maimum detection Jar: 6 Jar; Capacity of tank: 4L; Test tube capacity: 120ml Ultrasonic frequency: 25KHZ; Ultrasonic power: 100W Weight: 45KG		661.00	
37	Refrigerant retrieve and fullfil machine	ZDT-AC375C		Recovering & Recycling; Recharging with electronic scale; Vacuum; New oil injuection; Automatic oil drain; Automatic air purge; Friendly interface easy to use; System language: English/Chinese; Special designed oil seperator to protect compressor; Maintenance message display; Optic & acoustic status indictors; Heavy duty filter drier; Tank pressure indicating; RS232 service port;		3010.00	
				Power supply: 220V/50Hz;			

38		ZDT-W320		Tank capacity: 12.5Kg; Compressor: 3/8; Working temperature: 11℃-47℃; Recycle speed: 240g/M; Dry tank: 68Kg; Accuracy: 0.001Kg; Vacuum pump pumping rate: 60L/M; Refrigerating fluid type: R134a or R12; Packing size: 116×68×68cm; Gross weight: 90Kg;		1097.00	
39	Hydraulic press machine	XH0811		20 Tons		248.00	
40	Welding machine	ZDT-NBC-315		Input voltage: 380V/3Phase, 50/60Hz; Max. power: 10KW; Instant load rate: 30%; Welding current: 50-315A; Welding wire diameter: 0.8mm, 1.0mm; Feeding wire equipment: inside; Net weight: 75Kg.		805.00	
41	Meson machine	FY9000		Power supply: AC380V, 50Hz, 3Phase; Input power: 22KV/A; Input current: 57A; Max welding current: 5800A; One-side welding thickness: 0.8+1.2mm; Welding timing range: 0.99min; Cable length: 2300+1900mm; Vacuum suction: 180Kg; Weight: 90Kg.		738.00	
42	Tail pipe	ZDT-QDH		Aluminum centrifugal fan, Power: 1-3P. Power supply: 380V , 50Hz; Air flow capacity: 1700m³/h. Low nosize, low power consumption, big air flow; Pipe diameter: Φ152mm.		201.00 per meter	
43		ZDT-QDJ		Aluminum centrifugal fan, Power: 1-3P. Power supply: 380V , 50Hz; Air flow capacity: 1700m³/h. Low nosize, low power consumption, big air flow.		1400.00	
				Luxury type: one electricity and one air		470.00	

44	Cord reel	ZYTБ-3L		Luxury type: one electricity and one air		770.00	
				Luxury type: two water, one air and one electricity		556.00	
45	Cord reel	ZYHR—2810 N		Air type: Air type cord reel(for air supply) Hose length: 10m pressure: 1.4MPa		97.00	
46		ZYCR-3NL		Wire type core reel(for wire, electric supply) 1. AC220V, 6A, 1.5mm ² , 3wires; 2. Air intake pipe: 0.85m; 3. Pipe length: 8m; 4. with direction buttons 5. Support can 120°rotation		97.00	
47		Repair light: TL-18W		Optional light for wire core reel Power consumption: 18W		28.00	
48	Spray gun	Basecoat (14 5193)		Gas consumption: 350 NI/min (12,4 cfm); Air intake: 2 bar (29 psi); Max operation temperature: 50℃; Max operation pressure: 10 bar (145 psi) Weight: 606 g Air inlet: G 1/4 a Size: 1,4 - 2,1		515.00	
49		Finish Coat/painting (159848)		Air consumption: 285 NI/min (10,1 cfm) Recommended pressure: 2,0 - 2,2 bar (29 - 31,9 psi) Max operation temperature: 50℃; Max operation pressure: 10 bar (145 psi) Air inlet: G 1/4 a		705.00	
				Nominal voltage: 220V, 1PH Nominal frequency: 50Hz			

50	Baking lamp	FY-3W		Nominal frequency: 50Hz Nominal current: 10A Nominal power consumption: 3300W Baking distance: 700MM Wire length: 5M		778.00	
51	Pneumatic wrench	01113A		Pneuma wrench, used for tyre screw, chassis and mechanical bolts with from M12-16		214.00	
52	Electric drill	GBM 10 RE					
53	Angle grinder	GWS 7-100		Power input: 2KW; Rotation speed: 6500 rpm Polishing mandrel: M14; Main handle: axle Pad diameter: 230mm; Weight(Without wires): 5.3 kg			
54	Polisher	GPO 12 CE		Power input: 1,250W; Rotation speed: 750 - 3000 rpm Polishing mandrel: M14; Grinding paper diameter: 180 mm Weight: 2.5 kg		385.00	
55	Nitrogen inflator	ZDT-330		Purity of Nitrogen: 95-99%; Pressure of compressor: 8-10KG; Output Nitrogen pressure: 0-8KG; Nitrogen production capacity: 55-70L/min; Tank capacity: 20L; Net weight: 60KG		872.00	
56	Tyre Inflation system	ZDT-OPS		Power supply: 100-220VAc50/60HZ; Power consumption: 10VA; Work temperature: -20°/-4°F to 70°C/158°F Maximum air suction pressure: 145PSI/10bar/1000KPa Tire inflation: 5-102PSI/0.3-7bar/35-700KPa Accuracy: 1PSI/0.07bar/7KPa; Minimum dispaly: 1PSI/0.1bar/5KPa Packing size: 500X290X170;		455.00	
				Power supply: 220V 50/60HZ Maximum consumption: 1100W±15%			

57	Combined sander and vacuum cleaner	T-45WS-C		Maximum consumption: 1100W +/-10% Suction power consumption: 250W; Air flow: 2.6m3/min Vacuum pressure: 2000mmH2O+-15% Current: 4.5A; Noise: 70dB Paper filter: 0.3u; Cloth filter: 6u Tank: 48L; Pipe length: 5 meters Size: 778x550x946mm(LxWxH)		1840.00	
58		ZDT-588		Tank: 50L Luxury movable cabinet; IC Automatic control; 1 in 2 functions; 5 inch and 6 holes grinding head; 8 holes square grinding head;		1480.00	
59	Spiral lobe(type) Air compressor system	Rotary screw air compressor S-18A		Introduced advanced overseas technology, exhaust capacity: 2.3m³/min, Nominal pressure: 8kg, motor power: 15KW, weight: 450Kg, size: 900*800*1140(include compressor, dryer, gas holder connection pipe and contactor)		6270.00	1 Unit
		Dryer SZD-3HTF		Back cooling and pre-cooling system, can be connected directly to refrigerant compressor which under 80℃. Air flow capacity: 2.5m³/min. Compressor motor: 0.5HP, Purifying rate: 99%			
		Air tank 1.0M3/10		Gas storage capacity: 1.0m³, pressure: 8Kg, Design temperature: 150℃, tank height: 2138mm, height of air inlet mouth: 724. Tank inside diameter: 850mm, Caliber: 40mm, connector: RP11/2, height of air exhaust mouth: 1654mm			
		Filter C-003/T-003/A-003		Air feed system: three-level filter.			
60	Air compressor	W-LD Q/R		Motor power: 22KW/30Hp; Tank: 320L; Air delivery: 3000L/min.; Pressure: 8PSI, 10bar; Air cylinder: 155*2 & 82*2	2.754m³	2980.00	

60	(Separate)	WT-0.970		Air cylinder: 100 L & 0.2 L; Route: 116mm; Rotation speed: 860r/min; Gross weight: 820kg; Packing size: 1800*900*1700mm	820KG	2900.00	
61	Waste gas analyzer	ZDT-5G		CO: Measurement range0~10.0 10-2(%) CO2: Measurement range0~20.0 10-2(%) HC: Measurement range0~10000 10-6(ppm) O2: Measurement range0~25.0 10-2(%) NO: Measurement range0~5000 10-6(ppm) Oil temperature: 18℃~150℃ Rotation speed: 100~20000rpm		1810.00	
62	Brake lathe	ZDT-AC8700		Max. brake disc thickness: 40mm; Accuracy: ≤0.002-0.005; Brake disc accuracy: ≤0.001-0.005mm; Feed rate: 8.5mm/min; Electrical specifications: DC12V/1.5A; Power supply: 220V/50Hz; 110V/60Hz; Net weight: 50Kg;		1085.00	
63	Headlight detector	ZDT-D5T		Light intensity: 0~100000cd (distance light) Vertical direction: Up 2°~ Down 3°or Up 35cm/10m~ down 50cm/10m Horizontal direction: Left 3°~ right 3°Or left 50cm/10m~ right 50cm/10m Distance light center height indicate range: 50cm~130cm		790.00	
64	Light detector			Light intensity: 0~100000cd (distance light) Vertical direction: Up 2°~ Down 3°or Up 35cm/10m~ down 50cm/10m Horizontal direction: Left 3°~ right 3°Or left 50cm/10m~ right 50cm/10m Distance light center height indicate range: 50cm~130cm		7780.00	
65	Car fault diagnostic instrument	ZDT-3G		1. America auto: GM, FORD, CAN, CHRYSLER; 2. Europe auto: MERCEDES-BENZ, BMW, VW, Audi; 3. Asia auto: TOYOTA, HONDA, MITSUBISHI;		1830.00	
66		X431		1.6GHz Dual-core precessor Storge card --- 2GB.; Hard disk --- 16GB SSD Battery --- 7400mAh, 4 hours		564.00	

66				9.7" TFT IPS widescreen 130 Pixel (640 x480 resolution ratio) camera High speed hot printer; VGA&HDMI --- PPT/TV		304.00	
67	Sound level meter			For measurements of decibel		1080.00	
68	Car carpet cleaner	TJ618				688.00	
69	Paint mixing machine	ZDT-M68		1. Working power : AC220V/50Hz 2. Moto power : 800W (6 grades motor) 3. Stirring head amount: 68 pcs (can be tailor-made) 20 pcs for 3-Litre can (2 rows, each 10 pcs) 48 pcs for 1-Litre can (4 rows, each 12 pcs)		1735.00	
70	3D wheel aligner	ZDT-V3D		Measuring item Accuracy Measuring range Caster: ±0.05° ±20° Camber: ±0.02° ±20° Toe-in: ±0.02° ±20° Camber: ±0.02° ±10° Total toe-in: ±0.02° ±10° Thrust angle: ±0.02° ±5° Cower angle: ±0.02° ±5° Max. steering angle: ±0.08° ±50° Wheel distance: ±0.64cm(±0.25cm) <265cm(<105in) Axle distance: ±0.64cm(±0.25cm)		6300.00	
71	Speedometer tester			Include control system		5840.00	
72		ZDT-J 2400		Specifications of Suspension Test: Max load (single Axle): 2ton; Motor power: 2.5KW X2 Vibration Frequency: 0-23Hz; Specifications of Side-Slide Test		8045.00	

72	Test lane	ZDT-P2400		Max load (Single Axle): 2 ton; Measuring scope: ±12m/km Testing table size (Single slide table): 750*450mm(L*W); Testing table size (Double slide table): 2320*570mm(L*W).		5570.00	
73		ZDT-P1400		Technical parameter: Inspection speed: 5-15KM/H; Wheel distance: 880mm-2100mm; Max.axle load: 3.5T; Wheel brake force: 9000N; Side slip: ±15mm; Power supply: 220V,380V/50Hz; Power consumption: 1.2KW; Size: 4100*630*50mm.		7520.00	

CONTACT

triona.aleksei@gmail.com